

## Section 1: Product and company Information

#### 1.1 Product Identifier

Trade Name : R-404A

Substance/Mixture : CHF2CF3, CH3CF3, CH2FCF3

MSDS No : GCI-017

## 1.2 Details of the supplier of the safety data sheet

Name : Globcorp International Co W.L.L

Address : Shop No 52, Building 2527, Road 1535, Block

115, Hidd, Kingdom of Bahrain

Emergency number : +973-34026802/33701856/36487106

## 1.2 Product Composition / Information of ingredients

Substance Name : R-404A

Components	CAS-No	Concentration (% w/w)
1,1,1-Trifluoroethane	420-46-2	52
Pentafluoroethane	354-33-6	44
1,1,1,2-Tetrafluoroethane	811-97-2	4

## Section 2: Hazard Identification

Hazards identification : Liquefied gas

May cause frostbite and may displace oxygen and cause suffocation. Contains gas under pressure, may explode if heated. Product may cause

frostbite.

## Section 3: First Aid Measures

After Inhalation Remove victim to uncontaminated area wearing

self-contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial

respiration if breathing stopped.

After Skin contact The liquid may cause frostbite. If exposed to

liquid, immediately warm frostbite area with

warm water for at least 15 minutes.

After Eye contact Immediately flush eyes thoroughly with water for

at least 15 minutes.



# Refrigerant R-404A Safety Data Sheet GCI-017

Date of Issue: 01/01/2021 Revision date: 10/03/2021

After Ingestion Ingestion is unlikely because of the physical

properties and is not expected to be hazardous. Do not induce vomiting unless instructed to do so

by a physician.

Section 4: Firefighting Measures

Flammable class Non-flammable.

Specific hazards Contact with fire may cause containers to rupture

or explode.

Hazardous thermal decomposition products Decomposition products may include the

following: Carbon dioxide Carbon monoxide

Halogenated compounds

Carbonyl halides

Suitable extinguishing media Use appropriate extinguishing media for

surrounding fire.

Specific methods Stop flow of product if safe to do so.

Special protective equipment In confined space use self-contained breathing

apparatus.

Section 5: Handling and Storage

Storage Keep container below 52°C in a well ventilated

place. Maintain cylinders in an upright position

and ensure it is firmly secured.

Handling Prevent suck back and back feed into the

container.

Use only proper specified equipment which is

suitable for this product.

Refer to supplier's container handling

instructions. Contact your gas supplier if in doubt.

## Section 6: Exposure controls / Personal protection

Personal protection Ensure adequate ventilation.

**Exposure Controls:** 

Pentafluoroethane 1000 ppm TWA (8hr) 1,1,1-Trifluoroethane 1000 ppm TWA (8hr) 1,1,1,2-Tetrafluoroethane 1000 ppm TWA (8hr)



## Section 7: Physical and Chemical properties

Physical state at 20°C : Liquefied gas.

Color : Colorless.

Odor : Faint ethereal odor.

Molecular formula : CH2F2, CH2CF3

Molecular weight : 120

Melting point [°C] : -103

Boiling point [°C] : -47.8

Critical temperature [°C] : 72.4

Vapor pressure, 21°C : 182.9 psia

Relative density, gas (air=1) : 1.05 (25 °C)

Relative density, liquid (water=1) : 1.044 g/cm³ (25 °C)

Solubility in water [mg/I] : Unknown

# Section 8: Stability and Reactivity

Stability and reactivity Stable under normal conditions.

Can react strongly with oxidizing agents.

# Section 9: Toxicological Information

#### **Acute Toxicity:**

Product/Ingredient Name	Result	Species	Dose	Exposure
1,1,1-Trifluoroethane	LC50 Inhalation Gas	Rat	>54 pph	4 hours
	LC50 Inhalation Vapor	Rat	1080000 ppm	1 hour
Pentafluroethane	LC50 Inhalation Vapor	Rat	2910 g/m <sup>3</sup>	4 hours
1,1,1,2-Tetrafluoroethane	LC50 Inhalation Vapor	Rat	1500 h/m <sup>3</sup>	4 hours

# Section 10: Disposal Considerations

General : Do not discharge into any place where its accumulation could be dangerous or fatal.



# Refrigerant R-404A Safety Data Sheet GCI-017

Date of Issue: 01/01/2021 Revision date: 10/03/2021

# Section 11: Transport information

Transport document description

UN-NO (DOT)

Proper shipping name Hazard labels (DOT)

: UN3337, Refrigerant Gas R404A, 2.2

: UN3337

: Refrigerant gas R404A : 2.2 – Non-flammable gas



Other transport information Avoid transport on vehicles where the load space

is not separated from the driver's compartment. Ensure that the vehicle driver is aware of the potential hazards of the load and knows what to

do in case of an accident or emergency.

Ensure that containers are firmly secured.

Ensure cylinder valve is closed and not leaking. Ensure valve outlet cap nut or plug us correctly

fitted.

Ensure valve protection device is correctly fitted.

Ensure there is adequate ventilation. Compliance with applicable regulation.

## Section 12: Other Information

Before Transporting product containers

Ensure operators understand the oxygen enrichment.

Keep container in a well ventilated place.

Do no breathe the gas.

Ensure all national/local regulations are observed.

The hazard of asphyxiation is often overlooked and must be stressed during operator training.

Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.